

ULTRAFOAM™

Conforms to ASTM D6226

AUTOMATIC GAS PYCNOMETER FOR THE CHARACTERIZATION OF FOAMS

Added Capability

Correction For Cut Cells

Open cells % is estimated by remeasuring the volume of a cube after sectioning into eight parts. The UltraFoam's report gives both the open cell % and the corrected open cell % values.

Cell Compressibility

By automatically increasing pressure stepwise, the resulting series of compression % data extends the UltraFoam's range of usefulness to less rigid foams.

Cell Fracture

In a similar manner, the UltraFoam pycnometer has the important analytical ability for rigid foams that have fragile cell walls. In this mode, each step of increasing pressure is tested to see if the pressure change caused a permanent decrease in closed cell %. Results are presented as a series of fracture % versus pressure data.



The cell content of porous materials correlates with performance attributes such as strength, fluid exclusion (or inclusion) and insulating properties. Closed cells impart water resistance, thermal insulation, buoyancy and resilience. Open cells determine properties related to filtration, acoustics and wicking.

The analysis of this cellular structure is best performed by gas pycnometry. The gas, usually nitrogen or helium, quickly conditions the sample by carrying away blowing agents, moisture, air, etc. as it probes all cell cavities connected to the surface.

The standard technique used by the UltraFoam™ pycnometer is that of gas expansion from a calibrated sample chamber into a reference volume. The solid and closed cell volume of the sample is calculated from the relationship of the calibrated cell volumes and the pressures before and after expansion. The closed cell percentage is calculated from the solid volume and the measured geometric volume of a rectangular or cylindrical sample. Open cell % is calculated by difference (open cell % = 100% - closed cell %). Single or multiple measurements can be automatically performed, each taking but one or two minutes.

- Open Cell Content
- Closed Cell Content
- Correction for cut cells
- Cell Compressibility
- Cell Fracture
- Interchangeable sample cells
- Automatic reporting
- PC archiving of data.



Stereopycnometer™

Easily affordable, manual gas pycnometer. Easy to use, with results in just a few minutes. Ideal for rapid quality checks, field operation and teaching.

For more information:
Tel (561) 731-4999 or email qc.foams@quantachrome.com

© 2007 Quantachrome Corporation 0108 07163

Quantachrome
INSTRUMENTS

QUANTACHROME



Quantachrome Instruments' corporate headquarters in Boynton Beach, Florida.

Quantachrome®

Renowned innovator of ideas for today's porous materials community.

For over 40 years, Quantachrome's scientists and engineers have revolutionized measurement techniques and designed instrumentation to enable the accurate, precise, and reliable characterization of powdered and porous materials:

- Adsorption/Desorption Isotherms
- Surface Area Measurement
- Pore Size Distribution
- Chemisorption Studies
- Water Sorption Behavior
- Mercury Porosimetry
- True Solid Density
- Tapped Density

Not only are Quantachrome products the instruments of choice in academia, but the technology conceived and developed by our expert staff is applied in industrial laboratories worldwide, where research and engineering of new and improved porous materials is ongoing. Manufacturers also rely on porous materials characterization technology to more precisely specify bulk materials, to control quality, and to isolate the source of production problems with greater efficiency.

Quantachrome is also recognized as an excellent resource for authoritative analysis of your samples in our fully equipped, state-of-the-art powder characterization laboratory.



Quantachrome Instruments Application Laboratory.

CORPORATE HEADQUARTERS

Quantachrome Instruments

1900 Corporate Drive
 Boynton Beach, FL 33426 USA
 Phone: +1 800 989 2476
 +1 561 731-4999
 Fax: +1 561 732-9888
 E-mail: qc.sales@quantachrome.com
 www.quantachrome.com

CHINA

Quantachrome Representative Office

M806. Jingbao Garden
 183 Andingmenwai Street
 Beijing 100011, China
 Phone: +86 800 8100515
 +86 10 64400892
 +86 13 801191442
 Fax: +86 10 64400892
 www.quantachrome-china.com

EUROPE

Quantachrome UK Limited

Pale Lane Farm, Pale Lane
 Hartley Wintney
 Hook RG27 8BA, UK
 Phone: +44 (0) 1252819719
 Fax: +44 (0) 1252819901
 www.quantachrome.co.uk

EUROPE

Quantachrome GmbH & Co. KG

Rudolf-Diesel Str. 12
 85235 Odelzhausen, Germany
 Phone: +49 (0) 8134/93240
 Fax: +49 (0) 8134/932425
 www.quantachrome.de



Quantachrome Instruments' quality management system is certified to be in accordance with ISO9001:2000.

WORLDWIDE SALES AND SERVICE

Argentina	Mexico
Australia	Middle East
Austria	Morocco
Bahrain	Netherlands
Belarus	New Zealand
Belgium	Norway
Brazil	Oman
Bulgaria	Pakistan
Canada	Peru
Central America	Philippines
Chile	Poland
China	Portugal
Colombia	Puerto Rico
Croatia	Romania
Cyprus	Russia
Czech Republic	Saudi Arabia
Denmark	Singapore
Egypt	Slovak Republic
Estonia	Slovenia
Finland	South Africa
France	South Korea
Germany	Spain
Greece	Sri Lanka
Hungary	Sweden
India	Switzerland
Indonesia	Taiwan
Ireland	Tanzania
Israel	Thailand
Italy	Turkey
Jamaica	Ukraine
Japan	United Arab Emirates
Jordan	United Kingdom
Kuwait	Uruguay
Latin America	Uzbekistan
Latvia	Venezuela
Lithuania	Vietnam
Malaysia	

Quantachrome

INSTRUMENTS

Serving Porous
Materials and Powder
Characterization
Needs Since 1968



www.quantachrome.com

Trademarks and registered trademarks are the property of their respective owners.