

AUTOSORB[®]-IC/MS

COMPLETE GAS SORPTION ANALYZER WITH MASS SPECTROMETER



Quantachrome
INSTRUMENTS

QUANTACHROME

COMPLETE GAS SORPTION ANALYZER WITH MASS SPECTROMETER

Autosorb[®]-1-C/MS Benefits

- Combines gas detection by mass spectrometry with automatic gas sorption analysis to provide a more complete surface characterization of porous solids.
- Provides In-depth catalyst characterization, including micropore size determination in a single instrument.
- Achieves detailed identification of desorbed species under controlled heating rates and atmospheres.
- Requires little bench space because of Integrated design utilizing Autosorb's proven vacuum system.

AUTOSORB[®]-1-C/MS



The exposed surface of many powders is often found deep within individual particles. This fact has a tremendous impact on applications of powdered solids because, even for a single solid, not all surfaces are created equal. Real surfaces are heterogeneous and their properties vary from exterior to interior as well as from one surface patch to another. Such variations can be more fully quantified by means of a complete gas sorption analyzer such as the **Autosorb[®]-1-C/MS**.

Temperature Programming

During a chemisorption analysis, the total number of active sites, or the active surface area, is evaluated. If one heats up the sample, the chemisorbed species tend to desorb according to how strongly they were bound to the active sites to begin with. Weaker sites normally release their chemisorbed species at lower temperatures than stronger sites.

If the sample had two distinct types of active sites, heating would release gases at two different temperatures. To quantify these releases, one can increase the sample temperature linearly and monitor the evolution of gases in a number of ways. If only a single gas is evolved, one can simply monitor the rise in

pressure in a closed, pre-evacuated sample cell as a function of temperature. This could be regarded as a "Soak" Temperature Programmed Desorption (TPD) experiment.

If more than one species was desorbed, it would be necessary to identify each one as it is evolved from the sample. This can be done by attaching a Mass Spectrometer (MS) to the exit valve of the **Autosorb[®]-1-C** and performing the thermal desorption under a flow of inert or carrier gas. As such, this experiment would be termed Flow TPD, or Flow TPR if a reactive gas is used instead of an inert gas. With MS sampling rates in the order of seconds, this allows the evaluation in detail of fast-releasing "reactive" sites, or readsorption phenomena.

Moreover, a properly placed MS probe can sample gases from an evacuated chamber (Vacuum TPD). A clear advantage of Vacuum TPD is that desorbing species can reach the MS more quickly and without being affected by diffusion or readsorption effects through pore networks.

Over...



Quantachrome Instruments • 1900 Corporate Drive • Boynton Beach, FL 33426
(800) 989-2476 • (561) 731-4999 • FAX (561) 732-9888

www.quantachrome.com qc.sales@quantachrome.com

The AUTOSORB-1-C/MS

The Autosorb[®]-1-C/MS provides physisorption, chemisorption, flow or vacuum TPD and residual gas analysis (MS) capabilities in a single unit.

1. Temperature programmed furnace: 1°C steps up to 1000°C with ramp rates up to 50°C per minute.
2. Quartz flow-through cell for chemisorption studies.
3. Floating cell guard.
4. Flexible positioning of quadrupole sensor and electronics control unit for various models of residual gas analyzers.
5. Needle valve for mass spectrometer or optional diversion valve for GC port.



Autosorb[®]-1-C/MS SPECIFICATIONS

General

Range:	1 to 200 amu (optional)
Detectors:	Faraday Cup Electron Multiplier (optional)
Ion Source:	Open or Closed
Maximum Operating Pressure:	1×10^{-4} (open ion source) 1×10^{-2} (closed ion source)
Resolution:	<10% of Valley (per AVS Standard 2.3)
Sensitivity:	2×10^{-4} amps/torr (open ion source)
Min. Detectable Partial Pressure:	Faraday Cup (2×10^{-11} torr) Electron Multiplier (5×10^{-14} torr)

Physical

ECU Operating Temperature:	0°C to 40°C
-----------------------------------	-------------

Compliance

CE Mark:	EMC 89/336/EEC (electromagnetic compatibility) 72/23/EEC Low Voltage Directive
-----------------	-----------------------------------------------------------------------------------------

SELECTED APPLICATIONS

Physisorption Studies
Micropore Analysis
Mesopore Analysis
Fractal Dimensions
Chemisorption Tests
Carbon Reactivity
Catalyst Dispersion
Surface Acidity and Basicity
Other



Quantachrome Instruments' corporate headquarters in Boynton Beach, Florida.

Quantachrome®

Renowned innovator of ideas for today's porous materials community.

For over 40 years, Quantachrome's scientists and engineers have revolutionized measurement techniques and designed instrumentation to enable the accurate, precise, and reliable characterization of powdered and porous materials:

- Adsorption/Desorption Isotherms
- Surface Area Measurement
- Pore Size Distribution
- Chemisorption Studies
- Water Sorption Behavior
- Mercury Porosimetry
- True Solid Density
- Tapped Density

Not only are Quantachrome products the instruments of choice in academia, but the technology conceived and developed by our expert staff is applied in industrial laboratories worldwide, where research and engineering of new and improved porous materials is ongoing. Manufacturers also rely on porous materials characterization technology to more precisely specify bulk materials, to control quality, and to isolate the source of production problems with greater efficiency.

Quantachrome is also recognized as an excellent resource for authoritative analysis of your samples in our fully equipped, state-of-the-art powder characterization laboratory.



Quantachrome Instruments Application Laboratory.

CORPORATE HEADQUARTERS

Quantachrome Instruments

1900 Corporate Drive
 Boynton Beach, FL 33426 USA
 Phone: +1 800 989 2476
 +1 561 731-4999
 Fax: +1 561 732-9888
 E-mail: qc.sales@quantachrome.com
 www.quantachrome.com

CHINA

Quantachrome Representative Office

M806. Jingbao Garden
 183 Andingmenwai Street
 Beijing 100011, China
 Phone: +86 800 8100515
 +86 10 64400892
 +86 13 801191442
 Fax: +86 10 64400892
 www.quantachrome-china.com

EUROPE

Quantachrome UK Limited

Pale Lane Farm, Pale Lane
 Hartley Wintney
 Hook RG27 8BA, UK
 Phone: +44 (0) 1252819719
 Fax: +44 (0) 1252819901
 www.quantachrome.co.uk

EUROPE

Quantachrome GmbH & Co. KG

Rudolf-Diesel Str. 12
 85235 Odelzhausen, Germany
 Phone: +49 (0) 8134/93240
 Fax: +49 (0) 8134/932425
 www.quantachrome.de



Quantachrome Instruments' quality management system is certified to be in accordance with ISO9001:2000.

WORLDWIDE SALES AND SERVICE

Argentina	Mexico
Australia	Middle East
Austria	Morocco
Bahrain	Netherlands
Belarus	New Zealand
Belgium	Norway
Brazil	Oman
Bulgaria	Pakistan
Canada	Peru
Central America	Philippines
Chile	Poland
China	Portugal
Colombia	Puerto Rico
Croatia	Romania
Cyprus	Russia
Czech Republic	Saudi Arabia
Denmark	Singapore
Egypt	Slovak Republic
Estonia	Slovenia
Finland	South Africa
France	South Korea
Germany	Spain
Greece	Sri Lanka
Hungary	Sweden
India	Switzerland
Indonesia	Taiwan
Ireland	Tanzania
Israel	Thailand
Italy	Turkey
Jamaica	Ukraine
Japan	United Arab Emirates
Jordan	United Kingdom
Kuwait	Uruguay
Latin America	Uzbekistan
Latvia	Venezuela
Lithuania	Vietnam
Malaysia	

Quantachrome

INSTRUMENTS

Serving Porous
Materials and Powder
Characterization
Needs Since 1968



www.quantachrome.com

Trademarks and registered trademarks are the property of their respective owners.